



FM Device Socket, Austria

Order number: 7310064  
Type: E810

- According to IEC 60670 tested by ÖVE
- Installation of pre-assembled device combinations possible
- Can be combined as required

Dimensions

|                |            |
|----------------|------------|
| Depth          | 45 - 45 mm |
| Height         | 72 mm      |
| Internal depth | 43 mm      |
| Length         | 72 mm      |
| Width          | 73,4 mm    |

Environmental conditions

|                                         |        |
|-----------------------------------------|--------|
| Ambient temperature (24h)               | 35 °C  |
| Ambient temperature (maximum)           | 40 °C  |
| Ambient temperature (minimum)           | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 %   |
| Max. rel. humidity at 40°C              | 50 %   |

Material

|                 |    |
|-----------------|----|
| Socket material | PS |
|-----------------|----|

Properties

|                           |       |
|---------------------------|-------|
| Can be lead sealed        | -     |
| Colour                    | Black |
| Degree of protection (IP) | IP20  |
| Free of heavy metals      | true  |
| Halogen-free              | true  |
| Installation type         | FM    |
| PVC-free                  | true  |
| Silicone-free             | true  |
| Stackable                 | -     |
| Weather-resistant         | -     |

Technical features

|                    |         |
|--------------------|---------|
| Design voltage     | 400 V   |
| max. cross section | 2,5 mm² |
| Pipe entry M20     | 7       |
| Pipe entry M25     | 1       |

Certificates & standards

|                |        |
|----------------|--------|
| CE             | true   |
| Glow wire test | 650 °C |
| ÖVE            | true   |
| REACH          | true   |
| RoHS           | true   |
| Standards      |        |
| VDE            | -      |

Accessories

|               |      |
|---------------|------|
| Equipped with | None |
|---------------|------|