

SM automate box, 4 modules

Order number: 7260012  
Type: KV04



- Compact housing - For clear installation
- With 2, 4 or 6 modules
  - Available without and with clamps
  - For devices up to 63A
  - With back panel
  - With integrated standard profile rail

suitable for:

| Dimensions     |        | Environmental conditions                |        |
|----------------|--------|-----------------------------------------|--------|
| Depth          | 65 mm  | Ambient temperature (24h)               | 35 °C  |
| Height         | 160 mm | Ambient temperature (maximum)           | 40 °C  |
| Width          | 94 mm  | Ambient temperature (minimum)           | -25 °C |
|                |        | Max. rel. humidity at 25°C (short term) | 95 %   |
|                |        | Max. rel. humidity at 40°C              | 50 %   |
| Material       |        |                                         |        |
| Box material   | PS     |                                         |        |
| Cover material | PS     |                                         |        |

Properties

|                           |                     |
|---------------------------|---------------------|
| Can be lead sealed        | -                   |
| Colour                    | White               |
| Degree of protection (IP) | IP30                |
| Free of heavy metals      | true                |
| Halogen-free              | -                   |
| Installation type         | SM                  |
| Insulation                | Protection class II |
| Number of compartments    | 4                   |
| Number of rows            | 1                   |
| PVC-free                  | true                |
| Silicone-free             | true                |
| Stackable                 | -                   |
| Weather-resistant         | -                   |

Technical features

|                |       |
|----------------|-------|
| Design voltage | 400 V |
|----------------|-------|

Certificates & standards

|                |        |
|----------------|--------|
| CE             | -      |
| Glow wire test | 750 °C |
| REACH          | true   |
| RoHS           | true   |
| VDE            | -      |

Accessories

|               |      |
|---------------|------|
| Equipped with | none |
|---------------|------|