

AK 4 MIT SIX LOBE SCHRAUBE - Connection terminal block



0711409

<https://www.phoenixcontact.com/de/produkte/0711409>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connection terminal block, nominal current: 32 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.5 mm² - 6 mm², mounting: Neutral busbar, color: silver

AK 4 MIT SIX LOBE SCHRAUBE - Connection terminal block



0711409

<https://www.phoenixcontact.com/de/produkte/0711409>

Technical data

Product properties

Product type	Pick-off terminal
Number of connections	1
Number of rows	1

Electrical properties

Maximum load current	41 A (with 6 mm ² conductor cross section)
Maximum power dissipation for nominal condition	1.02 W
Nominal current I _N	32 A
Current carrying capacity of the neutral busbar	140 A

Connection data

Nominal cross section	4 mm ²
Maximum load current	41 A (with 6 mm ² conductor cross section)

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	16 mm
Conductor cross section rigid	0.5 mm ² ... 6 mm ²
Cross section AWG	20 ... 10 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	20 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²
2 conductors with same cross section, solid	0.5 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.5 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.5 mm ² ... 2.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 2.5 mm ²
Nominal current	32 A
Maximum load current	41 A (with 6 mm ² conductor cross section)
Nominal cross section	4 mm ²

Dimensions

AK 4 MIT SIX LOBE SCHRAUBE - Connection terminal block



0711409

<https://www.phoenixcontact.com/de/produkte/0711409>

Dimensional drawing	
Width	7 mm
Height	23.5 mm
Depth	26 mm
Length	23.5 mm

Material specifications

Color	silver
Flammability rating according to UL 94	V2

Mounting

Mounting type	Neutral busbar
---------------	----------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de