



SMART CONNECT KNX viega

Product	Order number	VE	PP
 SMART CONNECT KNX viega DRA, TP1	1-000A-008	1	1

Technical data

Rated voltage:	DC 24 V to 30 V
Power consumption:	2 W (24 V DC external supply)
Ambient temperature:	0 °C to +45 °C
KNX communication:	KNX/TP, S-Mode
KNX medium:	TP1-256
IP communication:	Ethernet 10/100 BaseT
Connections:	2x RJ45 (integrated switch) Connection and branching terminals for KNX and 24 V
Dimensions:	2 HP (DRA plus)

Information

Integrate the innovative single-room control Fonterra Smart Control by viega via the gateway SMART CONNECT KNX viega into the KNX system.

Features:

- Support of 5 base stations each with up to 8 room temperature controllers and 12 outlets
- Room temperature control
- Switching between heating and cooling mode
- Power level control
- Absence control
- System information such as error messages, actual temperature or updates from viega
- Simple integration in KNX (can be completely configured via ETS)
- Extensions via firmware updates

If you wish to use the SMART CONNECT KNX viega, you must use Fonterra Smart Control for Fonterra surface temperature regulating systems in Version 3 or higher with firmware version 2.8-4.43 or higher, supplied by Viega GmbH & Co. KG.

The product may slightly differ from the illustration.

12.01.2022

**ise Individuelle Software
und Elektronik GmbH**
Osterstraße 15
26122 Oldenburg
Germany

Phone: +49 441-680 06-11
Fax: +49 441-680 06-15
E-mail: sales@ise.de
Web: www.ise.de