



Manuals and documents in further languages:  
[https://eltako.com/redirect/WSZ155DSS-16A\\_MID](https://eltako.com/redirect/WSZ155DSS-16A_MID)

Technical data page 10-34.

# WSZ155DSS-16A MID

MID

Portable single-phase energy meter with German type plug and coupling (Type F). Suitable for indoor and outdoor use. MID-compliant and therefore approved for use for billing purposes. Maximum current 16 A. Protection class IP54. Standby loss 0,4 watt only. Protection class housing: IP68, protection class plug/coupling: IP44.

Housing dimensions 155 x 60 x 82 mm, connection cable 1.5 m (including plug and coupling). Accuracy class B (1%). This portable single-phase energy meter measures active energy by means of the current between input and output. The internal power consumption of 0.4 watt active power is neither metered nor indicated. **The display changes cyclically every 10 seconds between the accumulated active energy in kWh and the instantaneous consumption in kWh.** The start current is 20 mA. The display can only be read when the power supply is on. However, the consumption is saved to a non-volatile memory and is displayed immediately after a power failure. The digital display has 7 digits. Two decimal places are indicated up to 99999.99 kWh. Above 100000.0 kWh there is only one decimal place. The mobile single phase meter is equipped with a mounting bracket for easy installation. This can easily be removed if not necessary. The power consumption is shown with a LED that flashes 2000 times per kWh.

|                   |                                         |                   |              |
|-------------------|-----------------------------------------|-------------------|--------------|
| WSZ155DSS-16A MID | Portable single-phase energy meter, MID | Art. No. 28016115 | 126,98 €/pc. |
|-------------------|-----------------------------------------|-------------------|--------------|