

DECENTRALISED ACTUATOR WITH SENSOR INPUT 230 V PL-SM1L



Manuals and documents in further languages:
<https://eltako.com/redirect/PL-SM1L>

PC software SIENNA-Professional
page 4-9.

Typical connections on page 4-10.

PL-SM1L



Powerline sensor input with 1 channel. 53 x 43 mm, 25 mm deep for mounting in 58 mm switch boxes. Sensor input 230 V. Standby loss only 0,5 watt. To control and switch at different places.

When pressed, the sensor input acts on all actuators with the same address or as a central pushbutton if element address 0 is used.

Two rotary switches are located on the front for address assignment:

The left rotary switch defines the group address g with 16 alphabetical values from A to P.

The right rotary switch defines the element address e with 16 numerical values from 0 to 15.

Above it is a slide switch which acts **as a configuration switch with positions 0, 1 and 2.**

Position 0: Sensor input with reset function as pushbutton.

Position 1: Sensor input functions as NO contact.

Position 2: A change-over switch is evaluated as a pushbutton.

All entries and configurations can also be accessed via the mains using the PC software SIENNA Professional (see page 4-9).

To the left of the rotary switches is a red LED which indicates all activities.

Next to it is a reset pushbutton and to the right of that is a service pin. For functions, please refer to the operating instructions.

The terminals located above are plug-in terminals for conductor cross-sections of 0.2 mm² to 1.5 mm².

PL-SM1L	Powerline sensor input 230 V	Art. No. 31100007	109,20 €/pc.
---------	------------------------------	-------------------	--------------